



COMPACT IN TRAVELLING POSITION

The design of **CTE ZED 15.2** has been studied to enable access and transit even in confined spaces, thanks to its extreme compactness.





TECHNICAL DATA

- Lower arm with an articulated element + telescopic boom with one extension
- 360° continuous turret rotation
- Electrohydraulic proportional controls from ground and basket
- Engine start and stop from ground and basket
- Anti-slip aluminium flatbed deck
- Basket base in composite material and aluminum guardrails (1400x700x1100 mm) and 230 kg capacity. Available VTR basket with 200 kg capacity
- Basket rotation 60° left + 60° right
- Automatic hydraulically actioned basket levelling
- 4 hydraulic outriggers with ground pressure sensors
- Load cell managed basket capacity
- Possibility to work on slopes up to 2,5%
- Hydraulic system operated by electromagnetic clutch
- 230 V AC in the basket
- Buzzer indicating electromagnetic clutch engaged
- Hour meter
- Standard boom colour blue (RAL 5017) or white (RAL 9003)
- EN 280:2013 CE certified
- European Homologation certificate

CTE S.p.A.

Headquarter

7 Via Čaproni Rovereto (TN) IT, 38068

Ph. +39 0464 48.50.50 **Fax** +39 0464 48.50.99 info@ctelift.com **www.ctelift.com**

Factory

5 Loc. Terramatta Rivoli Veronese (VR) IT, 37010 **CTE UK Ltd**

Enderby Leicestershire - UK

